



FUSION2GO XR RV









High-Performance Cell Phone Signal Booster for RVs, Motorhomes and Trailers

Overview

Powerful and rugged, the Fusion2Go XR RV cell phone signal booster from SureCall increases the range of 5G and 4G LTE devices inside any RV. It boosts voice, text, and data signals for all US carriers with the most powerful vehicle amplifier on the market to provide strong cellular connectivity for mobile devices. Featuring the maximum transmit power allowed by the FCC in a moving vehicle, the XR RV maintains connection to the furthest cell towers.

The high-performing kit includes an omni-directional exterior antenna that captures signal from all directions. The intelligent booster system locks onto the carriers' signals using patented smart technology to maintain connection. The interior antenna delivers boosted signal to all cellular devices in range while simultaneously returning optimized signal back to the tower. The stronger connection results in fewer dropped calls, improved call clarity, faster data speeds and less buffering while streaming and browsing.

- Boosts 5G and 4G LTE voice, text, and data inside any RV, maximizing signal performance and extending range in remote areas for all cellular phones and devices.
- Works with all US cell carriers, including Verizon, AT&T, T-Mobile, Straight Talk, US Cellular and more.
- Supports multiple simultaneous devices, including hotspots, while extending battery life.
- SUPERCHARGED signal booster delivers reliable connectivity in remote locations with fewer dropped calls, improved call clarity, and faster data speeds while streaming and browsing.
- Durable high-gain exterior omni-directional antenna can be mounted to a ladder or short mast on any RV.
- Simple setup with 'SureCall' mobile app determines best antenna position to provide maximum performance. Available in Google Play or Apple's App Store.
- Designed, assembled and tested in the USA. Kit includes lifetime 100% US-based tech support and industry leading 3-year warranty.

Kit contents

High-performance Fusion2Go XR booster, high-gain exterior fiberglass enclosed antenna with mounting hardware, 40 ft SC240 low-loss cable, interior whip antenna, air vent phone mount clip, AC and DC power supplies, and quick setup guide.



Exterior Antenna



Coax Cable (40 ft)



Signal booster



Inside whip antenna



AC power adapter



Fusion2Go XR RV booster kit for RVs

Key Specifications

Uplink Frequency 698-716 / 776-787 / 824-849 / Ranges (MHz): 1710-1780 / 1850-1915

Downlink Frequency 728-746 / 746-757 / 869-894 / Ranges (MHz): 1930-1995 / 2110-2180

Supported Standards 5G, 4G, LTE cellular standards

Cellular bands: 12 / 17 / 13 / 5 / 2 / 25 / 4

Max Gain: 50 dB

Gain Adjustment: 20 dB (Automatic)

Max Uplink Power: 29.0 dBm

Power Consumption: \leq 12W

VSWR: \leq 2.0

RF Connectors: FME Male (both ends)

➤ Patent No. US 8,867,572 B1; US 9,100,839 B2



48346 Milmont Dr. Fremont, CA 94538 www.SureCall.com info@surecall.com 888-365-6283





FUSION2GO XR RV

High-Performance Cell Phone Signal Booster for RVs, Motorhomes and Trailers

Specifications

Uplink Frequency (MHz):	698-716 / 776-787 / 824-849 / 1850-1915 / 1710-1780
Downlink Frequency (MHz):	728-746 / 746-757 / 869-894 / 1930-1995 / 2110-2180
Supported Standards:	5G, 4G, LTE cellular standards
Cellular bands:	12 / 17 / 13 / 5 / 2 / 25 / 4
Maximum Gain:	50 dB
Input Impedance:	50 Ω
Gain Adjustment:	20 dB (Automatic)
Maximum Uplink Power:	29.0 dBm
DC Power:	6-15V
VSWR:	≤ 2.0
Exterior Cable:	SC-240 / 40 ft
RF Connectors:	FME Male (both ends)
Power Consumption:	≤ 12W
Operation Temperature:	-4° to +158° F
Dimensions:	5.625 x 4 x 1.125 inches
Weight:	1.43 lbs
Certification:	FCC: RSN-FUSION2GO5G Contains FCC ID: XPYNINAB1

